

Petroleum

PPDP11 MAXIMUS Drum Pump



Applications: Transferring petroleum products through low pressure hand or motor pumps, excellent flexibility at low temperatures when dispensing fuels, including ULP, and oils. UV stabilised.

Temperature: -5°C to +60°C
Cover: Black, PVC compound
Tube: Black, PVC Nitrile compound
Reinforcement: Fabric braid

Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
19	19.1	27	145	580	0.36
25	25.4	33	145	580	0.55

PHPS10 Marte AO



Applications: Suitable for suction and delivery of oil based fluids, diesel fuel, insecticides and aerial crop spray refilling. Very strong and features a high level of resistance to crushing and abrasion, resistance to atmospheric agents and most chemicals.

Temperature: -10°C to +60°C
Cover: Dark blue, slightly corrugated plasticised PVC
Tube: Dark blue, plasticised PVC
Reinforcement: Anti-shock rigid PVC helix

Size	ID mm	OD mm	WP psi	BP psi	B Rad mm	Vacuum %	Weight Kg/mtr
19	19.1	27.1	115	345	140	100	0.42
25	25.4	34.0	115	345	168	100	0.55
32	32.1	41.1	115	345	205	100	0.70
38	38.1	47.7	100	300	235	100	0.78
51	50.8	60.8	90	270	300	100	1.15
63	63.5	74.7	90	270	370	100	1.68
76	76.1	87.7	75	225	440	100	2.00
102	101.6	116.6	60	180	600	90	3.30

PHPS02 Blue Petroleum



Applications: Suction and delivery of Hydrocarbon materials such as diesel oils, grease, lubricants and most chemicals. Nitrile blend provides good flexibility and chemical resistance.

Temperature: -20°C to +60°C
Cover: Blue, slightly corrugated PVC Nitrile blend
Tube: Blue, smooth, PVC Nitrile blend
Reinforcement: Anti-shock rigid helix

Size	ID mm	OD mm	WP psi	BP psi	B Rad mm	Vacuum %	Weight Kg/mtr
25	25.4	32	75	225	80	85	0.39
32	32.1	39	75	225	100	85	0.51
38	38.1	46	65	195	150	85	0.65
51	50.8	60	65	195	200	85	1.10
63	63.5	75	60	180	250	85	1.50
76	76.2	87	55	165	300	85	1.80
102	101.6	115	55	165	375	85	3.01