

Air & Water

PPDW10 MAXIMUS Cold Washdown



Applications: General cold water washdown in parks, gardens, dairies and turf watering.

Temperature: -10°C to +60°C
Cover: White, smooth, PVC compound, 2 blue stripes
Tube: White, PVC compound
Reinforcement: Fabric braid

Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
12	12.7	19.0	145	580	0.22
19	20.5	26.5	145	580	0.40
25	25.1	34.0	145	580	0.58
32	32.1	42.5	145	580	0.85
38	38.1	49.5	145	580	1.11

PPDW11 Hotwash*



Applications: Conveyance of hot water under pressure and general hot washdown applications. The thermoplastic rubber smooth outer cover is highly resistant to lactic acids and fats, is UV resistant.

Temperature: -30°C to +90°C
Cover: White, smooth PVC compound
Tube: White, PVC compound
Reinforcement: Fabric braid

Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
12	12.7	19.7	290	1160	0.28
19	19.1	28.0	250	1015	0.48

* Product updated 05.2016, was PAHW

PPDW20 MAXIMUS Fire Reel



Applications: Fire hose designed especially for the use on fire reels, has a ribbed cover for greater abrasion resistance, and is UV resistant.

Conforming Standard: AS 1221

Temperature: -0°C to +60°C
Cover: Black, ribbed PVC compound
Tube: Black, PVC compound
Reinforcement: Fabric braid

Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
19	19.1	25.7	145	580	0.36
25	25.4	32.0	145	580	0.55