

# Product information

## CHDPB2051 - Danoil 9 SG Biofuel Hose

A hose specifically designed to handle Biodiesel products that contain esterified vegetable oils which have been found to damage most elastomers used. The nylon liner used gives excellent resistance to biodiesel, ethanol, unleaded petrol, MTBE and other high aromatics.

<b>Tube:</b>	Multiple layers of polyamide fabric
<b>Cover:</b>	Green PVC coated polyester cloth with white layline
<b>Reinforcement:</b>	Fabric: Polypropylene Inner Wire: Stainless Steel 316 Outer Wire: Galvanised Steel
<b>Temperature:</b>	-30°C to +80°C
<b>Conforming Standards:</b>	BS EN 13765: Type 3 Heavy duty hose meets International Maritime Org IBC Code US Coastguard requirements

**Branding:**



Size	ID mm	WP Kpa	BP Kpa	B Rad mm	Weight Kg/mtr
25	25.4	1400	5600	100	0.8
40	38.1	1400	5600	140	1.2
50	50.8	1400	5600	180	1.9
65	63.5	1400	5600	205	2.5
80	76.1	1400	5600	280	3.0
100L	101.6	1400	5600	395	5.2
100	101.6	1400	7000	405	6.4
150	152.4	1400	7000	510	10.7
200	203.2	1400	7000	760	15.0
250	254.0	1050	5250	915	20.5