

# PVC

## DUPAS10 Eolo Grey



**Applications:**

Light duty vacuum of air, fumes, gas, powders, sawdust, aerating and conditioning plants and wood working plants.

Smooth bore allows uninterrupted flow of medium.

**Conforming Standards:** UL 94-V2 for flame retardance

**Construction:** Smooth bore, grey PVC with rigid PVC anti-shock helix.

**Temperature:** -10°C to +50°C

Size	B Rad mm	Vacuum m H <sub>2</sub> O	Weight g/m
19	25	4.0	120
25	32	4.0	160
32	40	3.5	240
38	45	3.2	310
45	55	3.5	410
51	60	3.9	500
63	70	4.0	630
76	100	4.3	780
102	155	5.6	1280
127	190	5.8	1600
152	200	2.0	2000
203	240	1.5	2700
254	280	1.0	3600
305	330	1.0	4500

## DUPAS12 Blue PVC



**Applications:**

Suction and discharge of abrasive powders, fumes, shavings and vapours.

**Construction:** Corrugated bore, blue PVC with zinc plated steel wire helix

**Temperature:** -10°C to +50°C

Size	B Rad mm	Vacuum m H <sub>2</sub> O	Weight g/m
51	40	2.0	330
63	55	1.7	400
76	65	1.7	550
90	75	1.3	550
102	80	1.3	600
114	95	1.0	600
127	105	1.0	600
152	125	0.8	650
203	165	0.4	650
254	210	0.4	700
305	250	0.3	700