

PVC

DUPAS17 Barflo Industrial



Applications:

Medium to light duty vacuum and delivery, air seeding, excellent flexibility gives tight bend radius. UV stabilised.

Construction:

Smooth bore, corrugated black PVC cover.
(Sizes 12 and 16 are grey)

Temperature:

-5°C to +60°C

Size	B Rad mm	Vacuum m H ₂ O	Weight g/m
12	50	0.9	100
16	65	0.9	130
19	65	0.9	200
25	70	0.9	250
28	80	0.9	280
30.5	85	0.9	310
31.5	85	0.9	370
32	90	0.9	380
33.5	90	0.9	400
35	90	0.9	420
38	100	0.9	450
45	110	0.9	480
51	125	0.9	850
63	200	0.9	1000
76	250	0.9	1100
102	400	0.9	2000

DUPAS18 Barflo Heavy



Applications:

Heavy duty construction for collection of dust, saw dust, fumes and small particles. UV stabilised.

Construction:

Smooth bore, corrugated black PVC

Temperature:

-5°C to +60°C

Size	B Rad mm	Vacuum m H ₂ O	Weight g/m
31.5	125	0.95	420
38	130	0.95	550
45	135	0.95	750
51	175	0.95	1000
63	200	0.95	1100
76	300	0.95	1400
102	400	0.95	2500
127	450	0.95	3700

DUPAS19 Barflo Extra Heavy Duty



Applications:

Extra heavy duty vacuum and delivery, air seeding, excellent flexibility gives medium bend radius. UV stabilised.

Construction:

Smooth bore, corrugated black PVC.

Temperature:

-5°C to +60°C

Size	B Rad mm	Vacuum m H ₂ O	Weight g/m
45	200	1.0	1000